



Basic IP Phone

SIP-T9CM

Ideal for ITSPs, SMB and home users

- 3 SIP user accounts
- Auto-provision via TFTP, FTP and HTTP
- Zero Configuration
- PoE optional



Adjustable stand

Yealink SIP-T9CM is a feature-rich, cost-effective IP phone specially designed for ITSPs, small to medium businesses and residential application. It supports 3 user accounts, auto-provision, PoE, zero configuration and easy maintenance. As the basic model of the Yealink IP phones, SIP-T9CM offers high quality audio, a broad range of voice codecs and rich telephone features to general level users. Due to its excellent cost-performance ratio and high performance, it is absolutely a good choice for you!

Basic IP Phone

SIP-T9CM

Network Features

SIP v1(RFC2543), v2(RFC3261)
Registrar Server: 3 SIP user accounts
Power over Ethernet optional
Outbound Proxy mode
Peer-to-peer SIP link mode
TFTP/DHCP/PPPoE Client
Telnet/HTTP Server
DNS Client
NAT/DHCP Server
QoS

Voice Features

G.711, G.723.1, G.726,
G.729AB and GSM
VAD, CNG, AEC
Packet Loss Compensation
Adaptive Jitter Buffer

Telephony Features

Call Hold
Call Waiting
Call Transfer
Call Forward
Caller ID
Call List
Redial and Flash
Speed Dial
Phone Book
Volume Adjustment
Ring Tone Selection
3-way Conference
Speakerphone

Configuration

Web Browser
Console/Telnet
Keypad
Auto-provision

Firmware Upgrade

TFTP
Console
HTTP
Auto-provision

Dial Method

Direct IP call without SIP proxy
Dial number via SIP server
Dial URL via SIP server

DTMF Function

In-Band DTMF
Out-of-Band DTMF
SIP Info

IP Assignment

Static IP
DHCP
PPPoE

Security

HTTP 1.1 basic/digest authentication for Web setup
MD5 for SIP authentication (RFC 2069/RFC 2617)

NAT Traversal

STUN
UPnP

Physical Features

LCD: dual rows display, 2X16 dots
LEDs: Blue lights for Power and Hand free
Interface: 2 X RJ45 10/100M ports
Tilttable Stand: 30°/45°/60°
Dimension: 185 X 200 X 90mm
Weight: 0.77kg
Power adapter: Input: AC 100~240V
Output: DC 5V/1A
Operating humidity: 10~95%
Storage temperature: up to 60°C

Package Features

Qty/CTN: 10pcs
N.W/CTN: 11.43kg
G.W/CTN: 12.63kg
Gift box Size: 280 X 215 X 70mm
Carton Meas: 725 X 290 X 220mm

Certifications



Product Description

SIP-T9CM: Basic IP phone
SIP-T9P: Basic IP phone with PoE
SIP-T10: IP phone with value-added features
SIP-T10P: IP phone with value-added features and PoE

